

PanelView Plus 6 Terminals to PanelView Plus 7 Terminals Catalog Number Conversions

Topic	Page
About This Publication	1
Platform Replacements	2
Platform Comparisons	5
HMI Software Comparison	7
Application Migration	8
Terminal Selections	9
Catalog Number Conversion Tables	14
Accessories	22
Legacy Communication Support	22
Additional Resources	23

About This Publication

This publication provides information for converting PanelView™ Plus 6 terminals to these new generation terminals:

- PanelView Plus 7 Standard terminals
- PanelView Plus 7 Performance terminals

Platform Replacements

This section provides a comparison for platform replacement.

Table 1 - Platform Replacements

PanelView Plus 6 Terminals		PanelView Plus 7 Standard Terminals		PanelView Plus 7 Performance Terminals	
PanelView Plus 6 400 keypad	<ul style="list-style-type: none"> • 3.5-in. display size • Windows CE 6.0 • FactoryTalk® View ME (Machine Edition) station • Only keypad • Monochrome or color • No extended features • Ethernet, RS-232 • No communication module option • One USB port • One SD Card • AC or DC 	PanelView Plus 7 Standard 4-in. touch	<ul style="list-style-type: none"> • 4.3-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • No extended features • Ethernet (single or dual), DLR • No communication module option • Two USB ports • One SD Card • Only DC 	–	–
PanelView Plus 6 600 keypad and touch	<ul style="list-style-type: none"> • 5.7-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Keypad and touch • Monochrome or color • Extended features available • Ethernet, RS-232 • No communication module option • One USB port • One SD Card • AC or DC 	PanelView Plus 7 Standard 6-in. touch	<ul style="list-style-type: none"> • 5.7-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • No extended features • Ethernet (single or dual), DLR • No communication module option • Two USB ports • One SD Card • Only DC 	–	–
PanelView Plus 6 600 touch	<ul style="list-style-type: none"> • 5.7-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Monochrome or color • Extended features available • Ethernet, RS-232 • No communication module option • One USB port • One SD Card • AC or DC 	PanelView Plus 7 Standard 6-in. touch	<ul style="list-style-type: none"> • 5.7-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • No extended features • Ethernet (single or dual), DLR • No communication module option • Two USB ports • One SD Card • Only DC 	–	–

Table 1 - Platform Replacements (continued)

PanelView Plus 6 Terminals	PanelView Plus 7 Standard Terminals		PanelView Plus 7 Performance Terminals		
PanelView Plus 6 700 keypad and touch	<ul style="list-style-type: none"> • 6.5-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Keypad and touch • Color • Extended features available • Ethernet, RS-232 • Communication module option • Two USB ports, one mini USB port • One SD Card • AC or DC 	–	–	PanelView Plus 7 Performance 7-in. keypad and touch	<ul style="list-style-type: none"> • 6.5-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Keypad and touch • Color • Extended features • Dual Ethernet, DLR • No communication module option • Two USB ports • One SD Card • AC or DC
PanelView Plus 6 700 touch	<ul style="list-style-type: none"> • 6.5-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • Extended features available • Ethernet, RS-232 • Communication module option • Two USB ports, one mini USB port • One SD Card • AC or DC 	PanelView Plus 7 Standard 7-in. touch	<ul style="list-style-type: none"> • 6.5-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • No extended features • Ethernet (single or dual), DLR • No communication module option • Two USB ports • One SD Card • Only DC 	PanelView Plus 7 Performance 7-in. touch	<ul style="list-style-type: none"> • 6.5-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • Extended features • Dual Ethernet, DLR • No communication module option • Two USB ports • One SD Card • AC or DC
PanelView Plus 6 1000 keypad and touch	<ul style="list-style-type: none"> • 10.4-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Keypad and touch • Color • Extended features available • Ethernet, RS-232 • Communication module option • Two USB ports, one mini USB port • One SD Card • AC or DC 	–	–	PanelView Plus 7 Performance 10-in. keypad and touch	<ul style="list-style-type: none"> • 10.4-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Keypad and touch • Color • Extended features • Dual Ethernet, DLR • No communication module option • Two USB ports • One SD Card • AC or DC
PanelView Plus 6 1000 touch	<ul style="list-style-type: none"> • 10.4-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • Extended features available • Ethernet, RS-232 • Communication module option • Two USB ports, one mini USB port • One SD Card • AC or DC 	PanelView Plus 7 Standard 10-in. touch	<ul style="list-style-type: none"> • 10.4-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • No extended features • Ethernet (single or dual), DLR • No communication module option • Two USB ports • One SD Card • Only DC 	PanelView Plus 7 Performance 10-in. touch	<ul style="list-style-type: none"> • 10.4-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • Extended features • Dual Ethernet, DLR • No communication module option • Two USB ports • One SD Card • AC or DC

Table 1 - Platform Replacements (continued)

PanelView Plus 6 Terminals		PanelView Plus 7 Standard Terminals		PanelView Plus 7 Performance Terminals	
PanelView Plus 6 1200 keypad and touch	<ul style="list-style-type: none"> • 12.1-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Keypad and touch • Color • Extended features available • Ethernet, RS-232 • Communication module option • Two USB ports, one mini USB port • One SD Card • AC or DC 	—	—	PanelView Plus 7 Performance 12-in. keypad and touch	<ul style="list-style-type: none"> • 12.1-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Keypad and touch • Color • Extended features • Dual Ethernet, DLR • No communication module option • Two USB ports • One SD Card • AC or DC
PanelView Plus 6 1200 touch	<ul style="list-style-type: none"> • 12.1-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • Extended features available • Ethernet, RS-232 • Communication module option • Two USB ports, one mini USB port • One SD Card • AC or DC 	PanelView Plus 7 Standard 12-in. touch	<ul style="list-style-type: none"> • 12.1-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • No extended features • Ethernet (single or dual), DLR • No communication module option • Two USB ports • One SD Card • Only DC 	PanelView Plus 7 Performance 12-in. touch	<ul style="list-style-type: none"> • 12.1-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • Extended features • Dual Ethernet, DLR • No communication module option • Two USB ports • One SD Card • AC or DC
PanelView Plus 6 1500 keypad and touch	<ul style="list-style-type: none"> • 15-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Keypad and touch • Color • Extended features available • Ethernet, RS-232 • Communication module option • Two USB ports, one mini USB port • One SD Card • AC or DC 	—	—	PanelView Plus 7 Performance 15-in. keypad and touch	<ul style="list-style-type: none"> • 15-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Keypad and touch • Color • Extended features • Dual Ethernet, DLR • No communication module option • Two USB ports • One SD Card • AC or DC
PanelView Plus 6 1500 touch	<ul style="list-style-type: none"> • 15-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • Extended features available • Ethernet, RS-232 • Communication module option • Two USB port, one mini USB port • One SD Card • AC or DC 	PanelView Plus 7 Standard 12-in. touch	<ul style="list-style-type: none"> • 12.1-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • No extended features • Ethernet (single or dual), DLR • No communication module option • Two USB ports • One SD Card • Only DC 	PanelView Plus 7 Performance 15-in. touch	<ul style="list-style-type: none"> • 15-in. display size • Windows CE 6.0 • FactoryTalk View ME station • Only touch • Color • Extended features • Dual Ethernet, DLR • No communication module option • Two USB ports • One SD Card • AC or DC

Platform Comparisons

This table compares the differences between the new PanelView Plus 7 Standard and Performance terminals and the PanelView Plus 6 terminals.

Table 2 - PanelView Plus 6 and PanelView Plus 7 Standard and Performance Platform Comparison (400 and 600)

Feature	Platform	
	PanelView Plus 6 Terminals ⁽¹⁾ 400 and 600	PanelView Plus 7 Standard Terminals 4-in. and 6-in.
Operating system	Windows CE 6.0 includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support	Windows CE 6.0 includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support
FactoryTalk View ME station (runtime) software	Version 6.10 or later	Version 8.0 or later
FactoryTalk ViewPoint software	Yes	Version 7.0 or later
Application compatibility	Supports FactoryTalk View ME applications, version 3.2 or later ⁽²⁾	Supports FactoryTalk View ME applications, version 5.1 or later
RAM	256 MB DDR2 (chip onboard) 4264 MiB/s peak	512 MB RAM and 512 MB storage
Internal storage	512 MB nonvolatile (chip onboard)	512 MB nonvolatile memory (approx. 80 MB free user memory)
Interfaces		
Secure Digital (SD) Card slot	One Secure Digital high-capacity (SDHC) slot supports 1784-SDx cards	One SD card slot to store application files. Cat. Nos. 1784-SD1 (1 GB) and 1784-SD2 (2 GB)
USB ports	One USB-A, V2.0 high speed One USB-B, V2.0 high-speed, 4-pin	One USB-A, V2.0 high speed One USB-B, V2.0 high-speed, 4-pin
Keyboard and mouse compatibility	Yes	Yes
Communication Interfaces		
Ethernet	One 10/100 Mbps Auto-MDI/MDI-X	Cat. Nos. with 21: One 10/100 Base-T, Auto MDI/MDI-X with IEEE1588 support. Cat. Nos. with 22: Two 10/100Base-T, Auto MDI/MDI-X Ethernet ports that support Device Level Ring (DLR), linear, or star network topologies.
RS-232	One DB9	–
ControlNet	–	–
DH+™	–	–
DH-485	–	–
Remote I/O	–	–
DeviceNet	–	–

(1) The PanelView Plus 7 Performance terminals do not have a recommended conversion for the PanelView Plus 6 – 400 and 600 terminals.

(2) PanelView Plus 6 Compact terminals (2711PC-xxxxD8) support FactoryTalk View ME applications, version 5.1 or later.

Table 3 - PanelView Plus 6 and PanelView Plus 7 Standard and Performance Platform Comparison (700...1500)

Feature	Platform		
	PanelView Plus 6 Terminals 700, 1000, 1250, and 1500	PanelView Plus 7 Standard Terminals 7-in., 10-in., 12-in., and 15-in.	PanelView Plus 7 Performance Terminals 7-in., 10-in., 12-in., and 15-in.
Operating system	Windows CE 6.0 includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support	Windows CE 6.0 includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support	Windows CE 6.0 includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support
FactoryTalk View ME station (runtime) software	Version 6.0 or later	Version 8.0 or later	Version 8.0 or later
FactoryTalk ViewPoint software	Version 1.2 or later	Version 2.6 or later	Version 2.6 or later
Application compatibility	Supports FactoryTalk View ME applications, version 3.2 or later ⁽¹⁾	Supports FactoryTalk View ME applications, version 3.2 or later	Supports FactoryTalk View ME applications, version 3.2 or later
RAM	512 MB DDR2 (chip onboard) 4264 MiB/s peak	512 MB RAM and 512 MB storage	512 MB RAM and 512 MB storage
Internal storage	512 MB nonvolatile (chip onboard)	512 MB nonvolatile memory (approx. 80 MB free user memory)	512 MB nonvolatile memory (approx. 80 MB free user memory)
Interfaces			
Secure Digital (SD) Card slot	One Secure Digital high-capacity (SDHC) slot supports 1784-SDx cards	One SD card slot to store application files. Cat. Nos. 1784-SD1 (1 GB), 1784-SD2 (2 GB)	One SD card slot to store application files. Cat. Nos. 1784-SD1 (1 GB), 1784-SD2 (2 GB)
USB ports	Two USB-A, 2.0 high speed	One USB-A, V2.0 high speed One USB-B, V2.0 high-speed, 4-pin	Two USB 2.0 high-speed host ports (type A) support removable flash drives for external storage. One high-speed 2.0 device port (type B) which will be functional in a future release.
Keyboard and mouse compatibility	Yes	Yes	Yes
Communication Interfaces			
Ethernet	One 10/100 Mbps Auto-MDI/MDI-X	Cat. Nos. with 21: One 10/100 Base-T, Auto MDI/MDI-X with IEEE1588 support. Cat. Nos. with 22: Two 10/100Base-T, Auto MDI/MDI-X Ethernet ports that support Device Level Ring (DLR), linear, or star network topologies.	Two 10/100Base-T, Auto MDI/MDI-X Ethernet ports that support Device Level Ring (DLR), linear, or star network topologies
RS-232	One DB9	–	–
ControlNet	Add-on communication module	–	–
DH+™	Add-on communication module	–	–
DH-485	Add-on communication module	–	–
Remote I/O	–	–	–
DeviceNet	–	–	–

(1) PanelView Plus 6 Compact terminals (2711PC-xxxxxD8) support FactoryTalk View ME applications, version 5.1 or later.

HMI Software Comparison

The terminals run the Windows CE 6.0 operating system. The terminals run HMI applications and offer desktop access with extended features and file viewers. [Table 4](#) compares the features and extended features of the terminals.

Table 4 - Features and Extended Features

Features	PanelView Plus 6 Terminals 400...1500 (cat. nos. 2711P-xxxx8 and 2711P-RP8x)	PanelView Plus 6 Terminals 600 ⁽²⁾ ...1500 (cat. nos. 2711P-xxxx9 and 2711P-RP9x)	PanelView Plus 7 Standard Terminals (all cat. nos.)	PanelView Plus 7 Performance Terminals (all cat. nos.)
Standard Features				
FTP server	Yes ⁽¹⁾	Yes	Yes	Yes
VNC client server				
ActiveX controls ⁽¹⁾				
Third-party device support				
PDF reader				
Extended Features				
Internet Explorer web browser	No	Yes	No	Yes
Remote desktop connection				
Media player				
Microsoft Office file viewers <ul style="list-style-type: none"> • Excel • Image viewer • PowerPoint • Word 				
WordPad text editor				

(1) For a complete list of ActiveX controls, go to <https://rockwellautomation.custhelp.com/> and search the Knowledgebase for keywords 'ActiveX Support for PanelView Plus Terminals'.

(2) The remote desktop connection is not currently supported on PanelView Plus 6 (600) terminals with extended features.

[Table 5](#) compares the number of controllers, screens, and alarms functionality for each terminal.

Table 5 - Functionality

Functionality	PanelView Plus 6 Compact Terminals	PanelView Plus 7 Standard Terminals	PanelView Plus 6 Terminals	PanelView Plus 7 Performance Terminals
Controllers	1	1	No limitations.	No limitations.
Screens	25	25		
Alarms	200	200		

Application Migration

This section provides information for application migrations regarding screen resolution and communication options.

Resolution Differences

What impact does the different resolutions have when you run a PanelView Plus 6 application on a PanelView Plus 7 terminal?

- Except for the 7-in. and 15-in. terminals, all PanelView Plus 7 terminals have greater resolution.
- If you do not resize the application, the application runs in the top-left of the terminal. This issue is true for Windows CE or FactoryTalk View ME station platforms.
- If you do resize the application, you can go into each screen and adjust the position and layout of the objects. Especially when you convert from a normal screen to a wide screen.

If the terminal is set to allow desktop access and the shell type is set to open, these issues occur:

- The application does not resize to match the resolution of the screen.
- The application does not cover the screen. The Windows CE desktop is exposed and can be activated by touch.

If the terminal is set to disallow desktop access and the shell type is set to close, these issues occur:

- The application does not resize to match the resolution of the screen.
- The application does not cover the screen. The FactoryTalk View ME station is exposed, but cannot be activated by touch.

Application Migration for Communication

All PanelView Plus 6 terminal applications that are set to serial communication must be changed to Ethernet communication for PanelView Plus 7 terminals.

Terminal Selections

This section provides a description of the catalog numbers for the terminals.

PanelView Plus 6 Compact Terminal Selections

[Table 6](#) lists the catalog numbers available for the PanelView Plus 6 Compact 400...1000 terminals.

Table 6 - PanelView Plus 6 Compact Terminals

Cat. Nos.	Display		Input Type	Communication Ports		USB Ports		Power
	Size	Type		Ethernet	RS-232	Host	Device	
2711PC-K4M20D8	3.5-in.	Grayscale	Keypad	Yes	Yes	Yes	Yes	DC
2711PC-B4C20D8		Color	Keypad and Touch					
2711PC-B4C20D8-LR								
2711PC-T6M20D8	5.7-in.	Grayscale	Touch					
2711PC-T6C20D8		Color						
2711PC-T10C4D8	10.4 in.	Color	Touch					

PanelView Plus 6 – 400 and 600 Terminal Selections

The table shows the catalog number breakdown for the new PanelView Plus 6 – 400 and 600 terminals.

Bulletin	Input Type	Display Size	Display Type	Communication	Power	Operating System
2711P-	K = Keypad	4= 3.5 in.	C = Color	5 = RS-232, USB	A = AC	8 = Windows CE 6.0
	B = Keypad and Touch	6 = 5.7 in.	M = Grayscale	20 = Ethernet, RS-232, USB	D = DC	9 = Windows CE 6.0 with extended features
	T = Touch					

[Table 7](#) and [Table 8](#) list the catalog numbers available for the PanelView Plus 6 – 400 and 600 terminals without extended features and file viewers.

Table 7 - PanelView Plus 6 – 400 Terminals without Extended Features

Cat. Nos.		Display		Communication Ports		USB Ports		Input Power	Memory ⁽¹⁾	
Keypad	Keypad and Touch	Size	Type	RS-232	Ethernet	Host	Device		RAM	Nonvolatile
2711P-K4M5A8	–	3.5-in.	Grayscale	Yes	–	Yes	Yes	AC	256 MB	512 MB
2711P-K4M5D8	–							DC		
2711P-K4M20A8	–				Yes			AC		
2711P-K4M20D8	–							DC		
2711P-K4C5A8	2711P-B4C5A8	3.5-in.	Color	Yes	–	Yes	Yes	AC		
2711P-K4C5D8	2711P-B4C5D8							DC		
2711P-K4C20A8	2711P-B4C20A8				Yes			AC		
2711P-K4C20D8	2711P-B4C20D8							DC		

(1) The terminals support FactoryTalk View Machine Edition software, version 6.10 or later, and the Windows CE 6.0 operating system.

Table 8 - PanelView Plus 6 – 600 Terminals without Extended Features

Cat. Nos.			Display		Communication Ports		USB Ports		Input Power	Memory ⁽²⁾	
Keypad	Touch	Keypad and Touch	Size	Type	RS-232	Ethernet	Host	Device		RAM	Nonvolatile
2711P-K6M5A8	2711P-T6M5A8	2711P-B6M5A8	5.7-in.	Grayscale	Yes	–	Yes	Yes	AC	256 MB	512 MB
2711P-K6M5D8	2711P-T6M5D8	2711P-B6M5D8							DC		
2711P-K6M20A8	2711P-T6M20A8	2711P-B6M20A8				Yes			AC		
2711P-K6M20D8	2711P-T6M20D8	2711P-B6M20D8							DC		
2711P-K6C5A8 ⁽¹⁾	2711P-T6C5A8 ⁽¹⁾	2711P-B6C5A8 ⁽¹⁾	5.7-in.	Color	Yes	–	Yes	Yes	AC		
2711P-K6C5D8 ⁽¹⁾	2711P-T6C5D8 ⁽¹⁾	2711P-B6C5D8 ⁽¹⁾							DC		
2711P-K6C20A8 ⁽¹⁾	2711P-T6C20A8 ⁽¹⁾	2711P-B6C20A8 ⁽¹⁾				Yes			AC		
2711P-K6C20D8 ⁽¹⁾	2711P-T6C20D8 ⁽¹⁾	2711P-B6C20D8 ⁽¹⁾							DC		

(1) These terminals are available with extended features and file viewers by changing the 8 at the end of the catalog number to a 9; for example, 2711P-T6C5D9.

(2) The terminals support FactoryTalk View Machine Edition software, version 6.10 or later, and the Windows CE 6.0 operating system.

PanelView Plus 6 - 700...1500 Product Selections

The table shows the catalog number breakdown for the PanelView Plus 6 - 700...1500 terminals.

Bulletin Number	Input Type	Display Size	Display Type	Communication	Power	Operating System	Special Option
2711P-	K = Keypad	7 = 6.5 in.	C = Color	4 = Ethernet, RS-232, (2) USB Host	A = AC	8 = Windows CE 6.0 operating system	K = Conformal-coated
	B = Keypad and Touch	10 = 10.4 in.	M - Grayscale	20 = RS-232, (1) USB Host	D = DC	9 = Windows CE 6.0 operating system with extended features and viewers	
	T = Touch	12 = 12.1 in. 15 = 15 in.					

[Table 9](#) and [Table 10](#) list the catalog numbers available for the PanelView Plus 6 terminals.

Table 9 - PanelView Plus 6 – 700...1500 Terminals without Extended Features

Cat. No.			Display		Communication		Input Power	Memory RAM/Nonvolatile Storage
Keypad	Touch	Keypad/Touch	Size	Type	RS-232	Ethernet		
700 Model								
2711P-K7C4D8	2711P-T7C4D8	2711P-B7C4D8	6.5-in.	Color	Yes	Yes	DC	512 MB/512 MB
–	2711P-T7C4D8K	–					DC	
2711P-K7C4A8	2711P-T7C4A8	2711P-B7C4A8					AC	
1000 Model								
2711P-K10C4D8	2711P-T10C4D8	2711P-B10C4D8	10.4-in	Color	Yes	Yes	DC	512 MB/512 MB
2711P-K10C4A8	2711P-T10C4A8	2711P-B10C4A8					AC	
1250 Model								
2711P-K12C4D8	2711P-T12C4D8	2711P-B12C4D8	12.1-in	Color	Yes	Yes	DC	512 MB/512 MB
–	2711P-T12C4D8K	–					DC	
2711P-K12C4A8	2711P-T12C4A8	2711P-B12C4A8					AC	
1500 Model								
2711P-K15C4D8	2711P-T15C4D8	2711P-B15C4D8	15-in.	Color	Yes	Yes	DC	512 MB/512 MB
2711P-K15C4A8	2711P-T15C4A8	2711P-B15C4A8					AC	

Table 10 - PanelView Plus 6 – 700...1500 Terminals with Extended Features

Cat. No.			Display		Communication		Input Power	Memory RAM/Nonvolatile Storage
Keypad	Touch	Keypad/Touch	Size	Type	RS-232	Ethernet		
700 Model								
2711P-K7C4D9	2711P-T7C4D9	2711P-B7C4D9	6.5-in.	Color	Yes	Yes	DC	512 MB/512 MB
2711P-K7C4A9	2711P-T7C4A9	2711P-B7C4A9					AC	
1000 Model								
2711P-K10C4D9	2711P-T10C4D9	2711P-B10C4D9	10.4-in	Color	Yes	Yes	DC	512 MB/512 MB
2711P-K10C4A9	2711P-T10C4A9	2711P-B10C4A9					AC	
1250 Model								
2711P-K12C4D9	2711P-T12C4D9	2711P-B12C4D9	12.1-in	Color	Yes	Yes	DC	512 MB/512 MB
2711P-K12C4A9	2711P-T12C4A9	2711P-B12C4A9					AC	
1500 Model								
2711P-K15C4D9	2711P-T15C4D9	2711P-B15C4D9	15-in.	Color	Yes	Yes	DC	512 MB/512 MB
2711P-K15C4A9	2711P-T15C4A9	2711P-B15C4A9					AC	

PanelView Plus 7 Standard Terminals

The table shows the catalog number breakdown for the PanelView Plus 7 Standard terminals.

Bulletin	Input Type	Display Size	Display Type	Network	Power	Operating System	Model	-	Option
2711P-	T = Touch	4 = 4.3-in. 6 = 5.7-in. 7 = 6.5-in. 9 = 9.0-in. 10 = 10.4-in. 12 = 12.1-in. 15 = 15.0-in.	C = Color W = Wide aspect-ratio color	21 = Single Ethernet port 22 = Embedded switch/DLR	D = DC	8 = Windows CE	S = Standard ⁽¹⁾	-	B = No brand label

(1) The standard models support the Windows CE version 6.0 operating system with an FTP server, VNC client server, ActiveX controls, and PDF reader.

[Table 11](#) lists the catalog numbers available for the PanelView Plus 7 Standard terminals.

Table 11 - PanelView Plus 7 Standard Terminals Product Selections Without Extended Features

Cat. No. ⁽¹⁾	Display				Input Power	Ethernet Ports		Memory	
	Size	Type	Aspect Ratio	Pixels (W x H)		Single	DLR	RAM	Nonvolatile
2711P-T4W21D8S	4.3-in.	WQVGA	16:9	480 x 272	DC	Yes	-	512 MB	512 MB nonvolatile memory (approx. 80 MB free user memory)
2711P-T4W22D8S		TFT color				-	Yes		
2711P-T6C21D8S	5.7-in.	VGA	4:3	640 x 480		Yes	-		
2711P-T6C22D8S		TFT color				-	Yes		
2711P-T7C21D8S	6.5-in.	VGA	4:3	640 x 480		Yes	-		
2711P-T7C22D8S		TFT color				-	Yes		
2711P-T9W21D8S	9.0-in.	WVGA	5:3	800 x 480		Yes	-		
2711P-T9W22D8S		TFT color				-	Yes		
2711P-T10C21D8S	10.4-in.	SVGA	4:3	800 x 600		Yes	-		
2711P-T10C22D8S		TFT color				-	Yes		
2711P-T12W21D8S	12.1-in.	WXGA	16:10	1280 x 800		Yes	-		
2711P-T12W22D8S		TFT color				-	Yes		
2711P-T15C21D8S	15.0-in.	XGA	4:3	1024 x 768		Yes	-		
2711P-T15C22D8S		TFT color				-	Yes		

(1) Add -B to the end of a catalog number to order a terminal without the Allen-Bradley® logo and product identification; for example, 2711P-T9W21D8S-B.

PanelView Plus 7 Performance Terminals

The table shows the catalog number breakdown for the PanelView Plus 7 Performance terminals.

Bulletin	Input Type	Display Size	Display Type	Network	Power	Operating System	Model ⁽¹⁾	-	Option
2711P-	T = Touch	7 = 6.5-in.	C = Color	22 = Ethernet DLR ports	A = AC	9 = Windows CE	P = Performance	-	B = No brand identity
	B = Key and Touch	9 = 9-in.	W = Wide aspect ratio color		D = DC				
		10 = 10.4-in.							
		12 = 12.1-in.							
		15 = 15-in.							
		19 = 19-in.							

(1) Performance models support Windows CE 6.0 operating system with extended features: web browser, remote desktop connection, media player, Microsoft office file viewers, Word Pad text editor.

[Table 12](#) lists the catalog numbers available for the PanelView Plus 7 Performance terminals.

Table 12 - PanelView Plus 7 Performance Terminal Product Selections With Extended Features

Cat. No. ⁽¹⁾		Display		Ethernet	Power	Memory	
Touch	Key and Touch	Size	Type	DLR	AC or DC	RAM	Nonvolatile
2711P-T7C22D9P	2711P-B7C22D9P	6.5-in.	VGA TFT Color	Yes	DC	512 MB	512 MB nonvolatile memory (approx. 80 MB free user memory)
2711P-T7C22A9P	2711P-B7C22A9P				AC		
2711P-T9W22D9P	-	9-in. (wide)	WVGA TFT Color		DC		
2711P-T9W22A9P	-				AC		
2711P-T10C22D9P	2711P-B10C22D9P	10.4-in.	SVGA TFT Color		DC		
2711P-T10C22A9P	2711P-B10C22A9P				AC		
2711P-T12W22D9P	-	12.1-in. (wide)	WXGA TFT Color		DC		
2711P-T12W22A9P	-				AC		
2711P-T15C22D9P	2711P-B15C22D9P	15-in.	XGA TFT Color		DC		
2711P-T15C22A9P	2711P-B15C22A9P				AC		
2711P-T19C22D9P	-	19-in.	SXGA TFT Color		DC		
2711P-T19C22A9P	-				AC		

(1) Add -B to the end of a catalog number to order a terminal without the Allen-Bradley logo and product identification, for example, 2711P-T9W22D9P-B.

Catalog Number Conversion Tables

Tables in this section provide a direct catalog number conversion for your PanelView Plus 6 terminal to a compatible PanelView Plus 7 terminal.

Table 13 - PanelView Plus 6 Terminals (400) Primary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Primary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
400	2711P-K4M5A8	123 (4.86)	156 (6.15)	320 x 240	2711P-T4W21D8S	92 (3.62)	117 (4.61)	480 x 272	N/A	One Ethernet Port	The PanelView Plus 7 Standard terminals have the following application limits: <ul style="list-style-type: none"> • Max. screen count: 25 • Max. alarm messages: 200 • Max. number of controllers: 1 Communication for the PanelView Plus 7 Standard terminal is Ethernet (dual Ethernet ports are available). The PanelView Plus 7 Standard terminal input is only touch. The PanelView Plus 7 Standard terminal power input is only DC.
	2711P-K4M5D8										
	2711P-K4M20A8										
	2711P-K4M20D8										
	2711P-K4CA8										
	2711P-K4CD8										
	2711P-K4C20A8										
	2711P-K4C20D8										
	2711P-B4C5A8										
	2711P-B4C5D8										
	2711P-B4C20A8										
	2711P-B4C20D8										

Table 14 - PanelView Plus 6 Terminals (400) Secondary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
400	2711P-K4M5A8	123 (4.86)	156 (6.15)	320 x 240	2711P-B7C22A9P	142 (5.59)	237 (9.33)	640 x 480	N/A	Dual Ethernet Ports	PanelView Plus 7 Performance terminals communication is only Ethernet.
	2711P-K4M5D8										
	2711P-K4M20A8										
	2711P-K4M20D8										
	2711P-K4CA8										
	2711P-K4CD8										
	2711P-K4C20A8										
	2711P-K4C20D8										
	2711P-B4C5A8										
	2711P-B4C5D8										
	2711P-B4C20A8										
	2711P-B4C20D8										
	2711P-B7C22A9P										
	2711P-B7C22D9P										

Table 16 - PanelView Plus 6 Terminals (600) Secondary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
600 (1)	2711P-K6M5A8	142 (5.61)	241 (9.50)	320 x 240	2711P-B7C22A9P	142 (5.59)	237 (9.33)	640 x 480	N/A	Dual Ethernet Ports	PanelView Plus 7 Performance terminals communication is only Ethernet.
	2711P-K6M5D8		2711P-B7C22D9P		237 (9.33)						
	2711P-T6M5A8		156 (6.15)		2711P-T7C22A9P		184 (7.24)				
	2711P-T6M5D8		2711P-T7C22D9P		184 (7.24)						
	2711P-B6M5A8		241 (9.50)		2711P-B7C22A9P		237 (9.33)				
	2711P-B6M5D8				2711P-B7C22D9P						
	2711P-K6M20A8				2711P-B7C22A9P						
	2711P-K6M20D8		156 (6.15)		2711P-B7C22D9P		184 (7.24)				
	2711P-T6M20A8				2711P-T7C22A9P						
	2711P-T6M20D8				2711P-T7C22D9P						
	2711P-B6M20A8		241 (9.50)		2711P-B7C22A9P		237 (9.33)				
	2711P-B6M20D8				2711P-B7C22D9P						
	2711P-K6C5A8	2711P-B7C22A9P									
	2711P-K6C5D8	156 (6.15)	2711P-B7C22D9P	184 (7.24)							
	2711P-T6C5A8		2711P-T7C22A9P								
	2711P-T6C5D8		2711P-T7C22D9P								
	2711P-B6C5A8	241 (9.50)	2711P-B7C22A9P	237 (9.33)							
	2711P-B6C5D8		2711P-B7C22D9P								
	2711P-K6C20A8		2711P-B7C22A9P								
	2711P-K6C20D8	123 (4.86)	2711P-B7C22D9P	184 (7.24)							
	2711P-T6C20A8		2711P-T7C22A9P								
	2711P-T6C20D8		2711P-T7C22D9P								
	2711P-B6C20A8	142 (5.61)	2711P-B7C22A9P	237 (9.33)							
	2711P-B6C20D8		2711P-B7C22D9P								
	2711P-K6C5A9		2711P-B7C22A9P								
	2711P-K6C5D9	123 (4.86)	2711P-B7C22D9P	184 (7.24)							
	2711P-T6C5A9		2711P-T7C22A9P								
	2711P-T6C5D9		2711P-T7C22D9P								
	2711P-B6C5A9	142 (5.61)	2711P-B7C22A9P	237 (9.33)							
	2711P-B6C5D9		2711P-B7C22D9P								
2711P-K6C20A9	2711P-B7C22A9P										
2711P-K6C20D9	123 (4.86)	2711P-B7C22D9P	184 (7.24)								
2711P-T6C20A9		2711P-T7C22A9P									
2711P-T6C20D9		2711P-T7C22D9P									
2711P-B6C20A9	142 (5.61)	2711P-B7C22A9P	237 (9.33)								
2711P-B6C20D9		2711P-B7C22D9P									

(1) The terminals that are listed in the shaded area have extended features. The PanelView Plus 7 Standard terminal replacement option does not offer the extended features.

Table 17 - PanelView Plus 6 Terminals (700) Primary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Primary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
700 ⁽¹⁾	2711P-T7C4D8K	154 (6.08)	220 (8.67)	640 x 480	Conformal coated terminal. No primary replacement. See Table 18 for a secondary replacement option.						
	2711P-K7C4A8	167 (6.57)	264 (10.39)	640 x 480	2711P-B7C22A9P	142 (5.59)	237 (9.33)	640 x 480	2711P-RAAK7	Dual Ethernet Ports	The PanelView Plus 7 Performance 7-in. terminal is the primary replacement option for all PanelView Plus 6 700 terminals. PanelView Plus 7 Performance terminals communication is only Ethernet. Adapter plates are necessary for drop-in replacement.
	2711P-K7C4D8				2711P-B7C22D9P						
	2711P-T7C4A8	154 (6.08)	220 (8.67)		2711P-T7C22A9P		184 (7.24)		2711P-RAAT7		
	2711P-T7C4D8				2711P-T7C22D9P						
	2711P-B7C4A8	167 (6.57)	264 (10.39)		2711P-B7C22A9P		237 (9.33)		2711P-RAAK7		
	2711P-B7C4D8				2711P-B7C22D9P						
	2711P-K7C4A9	154 (6.08)	220 (8.67)		2711P-B7C22A9P		184 (7.24)		2711P-RAAT7		
	2711P-K7C4D9				2711P-B7C22D9P						
	2711P-T7C4A9	167 (6.57)	264 (10.39)		2711P-T7C22A9P		237 (9.33)		2711P-RAAK7		
	2711P-T7C4D9				2711P-T7C22D9P						
	2711P-B7C4A9	154 (6.08)	220 (8.67)		2711P-B7C22A9P		184 (7.24)		2711P-RAAT7		
	2711P-B7C4D9				2711P-B7C22D9P						

(1) The terminals that are listed in the shaded area have extended features.

Table 18 - PanelView Plus 6 Terminals (700) Secondary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
700 ⁽¹⁾	2711P-T7C4D8K	154 (6.08)	220 (8.67)	640 x 480	2711P-T7C22D9P ⁽²⁾	142 (5.59)	184 (7.24)	640 x 480	2711P-RAAT7	Dual Ethernet Ports	This option is not conformal-coated.
	2711P-K7C4A8	167 (6.57)	264 (10.39)	640 x 480	2711P-T7C21D8S	142 (5.59)	184 (7.24)	640 x 480	N/A	One Ethernet Port	The PanelView Plus 7 Standard terminals have the following application limits: • Max. screen count: 25 • Max. alarm messages: 200 • Max. number of controllers: 1 Communication for the PanelView Plus 7 Standard terminal is Ethernet (dual Ethernet ports are available). The PanelView Plus 7 Standard terminal input is only touch. The PanelView Plus 7 Standard terminal power input is only DC.
	2711P-K7C4D8										
	2711P-T7C4A8	154 (6.08)	220 (8.67)								
	2711P-T7C4D8										
	2711P-B7C4A8	167 (6.57)	264 (10.39)								
	2711P-B7C4D8										
	2711P-K7C4A9	154 (6.08)	220 (8.67)								
	2711P-K7C4D9										
	2711P-T7C4A9	167 (6.57)	264 (10.39)								
	2711P-T7C4D9										
	2711P-B7C4A9	154 (6.08)	220 (8.67)								
	2711P-B7C4D9										

(1) The terminals that are listed in the shaded area have extended features. The PanelView Plus 7 Standard terminal replacement option does not offer the extended features.

(2) This terminal does not have conformal coating, but can be a replacement if the replacement terminal no longer requires a conformal coating.

Table 19 - PanelView Plus 6 Terminals (1000) Primary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Primary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
1000 ⁽¹⁾	2711P-K10C4A8	224 (8.8)	375 (14.75)	640 x 480	2711P-B10C22A9P	224 (8.82)	335 (13.19)	800 x 600	2711P-RAAK10	Dual Ethernet Ports	The PanelView Plus 7 Performance 10-in. terminal is the primary replacement option for all PanelView Plus 6 1000 terminals. PanelView Plus 7 Performance terminals communication is only Ethernet. Adapter Plates are necessary for drop-in replacement.
	2711P-K10C4D8		305 (12.00)		2711P-B10C22D9P		269 (10.59)		2711P-RAAT10		
	2711P-T10C4A8				2711P-T10C22A9P						
	2711P-T10C4D8		375 (14.75)		2711P-B10C22A9P		335 (13.19)		2711P-RAAK10		
	2711P-B10C4A8				2711P-B10C22D9P						
	2711P-B10C4D8		305 (12.00)		2711P-T10C22A9P		269 (10.59)		2711P-RAAT10		
	2711P-K10C4A9				2711P-B10C22D9P						
	2711P-K10C4D9		375 (14.75)		2711P-T10C22A9P		335 (13.19)		2711P-RAAK10		
	2711P-T10C4A9				2711P-T10C22D9P						
	2711P-T10C4D9		375 (14.75)		2711P-B10C22A9P		335 (13.19)		2711P-RAAK10		
	2711P-B10C4A9				2711P-B10C22D9P						
	2711P-B10C4D9										

(1) The terminals that are listed in the shaded area have extended features.

Table 20 - PanelView Plus 6 Terminals (1000) Secondary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
1000 ⁽¹⁾	2711P-K10C4A8	224 (8.8)	375 (14.75)	640 x 480	2711P-T10C21D8S	224 (8.82)	269 (10.59)	800 x 600	N/A	One Ethernet Port	The PanelView Plus 7 Standard terminals have the following application limits: • Max. screen count: 25 • Max. alarm messages: 200 • Max. number of controllers: 1 Communication for the PanelView Plus 7 Standard terminal is Ethernet (dual Ethernet ports are available). The PanelView Plus 7 Standard terminal input is only touch. The PanelView Plus 7 Standard terminal power input is only DC.
	2711P-K10C4D8		305 (12.00)								
	2711P-T10C4A8										
	2711P-T10C4D8		375 (14.75)								
	2711P-B10C4A8										
	2711P-B10C4D8		305 (12.00)								
	2711P-K10C4A9										
	2711P-K10C4D9		375 (14.75)								
	2711P-T10C4A9										
	2711P-T10C4D9		375 (14.75)								
	2711P-B10C4A9										
	2711P-B10C4D9										

(1) The terminals that are listed in the shaded area have extended features. The PanelView Plus 7 Standard terminal replacement option does not offer the extended features.

Table 21 - PanelView Plus 6 Terminals (1250) Primary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Primary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
1250 ⁽¹⁾	2711P-T12C4D8K	257 (10.11)	338 (13.29)	800 x 600	Conformal coated terminal. No primary replacement. See Table 22 for a secondary replacement option.						
	2711P-K12C4A8	257 (10.11)	390 (15.35)	800 x 600	2711P-T12W22A9P	218 (8.58)	312 (12.28)	1280 x 800	2711P-RAAT12K	Dual Ethernet Ports	The PanelView Plus 7 Performance 12-in. terminal is the primary replacement option for all PanelView Plus 6 1250 terminals. The PanelView Plus 7 Performance 12-in. terminal is available only with Touch input. PanelView Plus 7 Performance terminals communication is only Ethernet. Adapter Plates are necessary for drop-in replacement.
	2711P-K12C4D8		2711P-T12W22D9P		2711P-RAAT12						
	2711P-T12C4A8		2711P-T12W22A9P								
	2711P-T12C4D8		2711P-T12W22D9P								
	2711P-B12C4A8		2711P-T12W22A9P								
	2711P-B12C4D8		2711P-T12W22D9P								
	2711P-K12C4A9		2711P-T12W22A9P								
	2711P-K12C4D9		2711P-T12W22D9P								
	2711P-T12C4A9		2711P-T12W22A9P								
	2711P-T12C4D9		2711P-T12W22D9P								
	2711P-B12C4A9		2711P-T12W22A9P								
	2711P-B12C4D9		2711P-T12W22D9P								

(1) The terminals that are listed in the shaded area have extended features.

Table 22 - PanelView Plus 6 Terminals (1250) Secondary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
1250 ⁽¹⁾	2711P-T12C4D8K	257 (10.11)	338 (13.29)	800 x 600	2711P-T12W22D9P ⁽²⁾	218 (8.58)	312 (12.28)	1280 x 800	2711P-RAAT12	Dual Ethernet Ports	This replacement option is not conformal-coated.
	2711P-K12C4A8	257 (10.11)	390 (15.35)	800 x 600	2711P-B15C22A9P	290 (11.42)	418 (16.46)	1024 x 768	2711P-RAAK15	Dual Ethernet Ports	The PanelView Plus 7 Performance 15-in. terminal is listed as a secondary replacement if you require a keypad. PanelView Plus 7 Performance terminals communication is only Ethernet.
	2711P-K12C4D8		2711P-B15C22D9P								
	2711P-T12C4A8		N/A		N/A	N/A	N/A	N/A			
	2711P-T12C4D8		N/A		N/A	N/A	N/A	N/A			
	2711P-B12C4A8		2711P-B15C22A9P								
	2711P-B12C4D8		2711P-B15C22D9P								
	2711P-K12C4A9		2711P-B15C22A9P								
	2711P-K12C4D9		2711P-B15C22D9P								
	2711P-T12C4A9		N/A		N/A	N/A	N/A	N/A			
	2711P-T12C4D9		2711P-B15C22A9P								
	2711P-B12C4A9		2711P-B15C22D9P								
	2711P-B12C4D9		2711P-B15C22D9P								

(1) The terminals that are listed in the shaded area have extended features.

(2) This terminal does not have conformal coating, but can be a replacement if the replacement terminal no longer requires a conformal coating.

Table 23 - PanelView Plus 6 Terminals (1500) Primary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Primary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
1500 ⁽¹⁾	2711P-K15C4A8	305 (12.00)	419 (16.50)	1024 x 768	2711P-B15C22A9P	290 (11.42)	418 (16.46)	1024 x 768	2711P-RAAK15	Dual Ethernet Ports	The PanelView Plus 7 Performance 15-in. terminal is the primary replacement option for all PanelView Plus 6 1500 terminals. PanelView Plus 7 Performance terminals communication is only Ethernet. Adapter Plates are necessary for drop-in replacement.
	2711P-K15C4D8		2711P-B15C22D9P		418 (16.46)		2711P-RAAK15				
	2711P-T15C4A8		391 (15.40)		353 (13.90)		2711P-RAAT15				
	2711P-T15C4D8		2711P-T15C22A9P		353 (13.90)		2711P-RAAT15				
	2711P-B15C4A8		2711P-B15C22A9P		418 (16.46)		2711P-RAAK15				
	2711P-B15C4D8		2711P-B15C22D9P		418 (16.46)		2711P-RAAK15				
	2711P-K15C4A9		2711P-B15C22A9P		418 (16.46)		2711P-RAAK15				
	2711P-K15C4D9		2711P-B15C22D9P		418 (16.46)		2711P-RAAK15				
	2711P-T15C4A9		2711P-T15C22A9P		353 (13.90)		2711P-RAAT15				
	2711P-T15C4D9		2711P-T15C22D9P		353 (13.90)		2711P-RAAT15				
	2711P-B15C4A9		2711P-B15C22A9P		418 (16.46)		2711P-RAAK15				
	2711P-B15C4D9		2711P-B15C22D9P		418 (16.46)		2711P-RAAK15				

(1) The terminals that are listed in the shaded area have extended features.

Table 24 - PanelView Plus 6 Terminals (1500) Secondary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
1500 ⁽¹⁾	2711P-K15C4A8	305 (12.00)	419 (16.50)	1024 x 768	2711P-T15C21D8S	290 (11.42)	353 (13.90)	1024 x 768	N/A	One Ethernet Port	The PanelView Plus 7 Standard terminals have the following application limits: • Max. screen count: 25 • Max. alarm messages: 200 • Max. number of controllers: 1 Communication for the PanelView Plus 7 Standard terminal is Ethernet (dual Ethernet ports are available). The PanelView Plus 7 Standard terminal input is only touch. The PanelView Plus 7 Standard terminal power input is only DC.
	2711P-K15C4D8										
	2711P-T15C4A8		391 (15.40)								
	2711P-T15C4D8		391 (15.40)								
	2711P-B15C4A8		419 (16.50)								
	2711P-B15C4D8		419 (16.50)								
	2711P-K15C4A9		419 (16.50)								
	2711P-K15C4D9		419 (16.50)								
	2711P-T15C4A9		391 (15.40)								
	2711P-T15C4D9		391 (15.40)								
	2711P-B15C4A9		419 (16.50)								
	2711P-B15C4D9		419 (16.50)								

(1) The terminals that are listed in the shaded area have extended features. The PanelView Plus 7 Standard terminal replacement option does not offer the extended features.

Table 25 - PanelView Plus 6 Compact Terminals (400, 600, and 1000) Primary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Primary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
400	2711PC-K4M20D8	123 (4.86)	156 (6.15)	320 x 240	2711P-T4W21D8S	92 (3.62)	117 (4.61)	480 x 272	N/A	One Ethernet Port	Communication for the PanelView Plus 7 Standard terminal is Ethernet (dual Ethernet ports are available). The PanelView Plus 7 Standard terminals have the same application limitations as the PanelView Plus 6 compact terminals. The PanelView Plus 7 Standard terminals are touch input.
	2711PC-B4C20D8				Low-reflective display. There is no primary replacement option. See Table 26 for a secondary replacement option.						
	2711PC-B4C20D8-LR										
600	2711PC-T6M20D8	224 (8.8)	305 (12.00)	640 x 480	2711P-T6C21D8S	123 (4.84)	156 (6.14)	640 x 480	N/A	One Ethernet Port	
	2711PC-T6C20D8										
1000	2711PC-T10C4D8	224 (8.8)	305 (12.00)	640 x 480	2711P-T10C21D8S	224 (8.82)	269 (10.59)	800 x 600			

Table 26 - PanelView Plus 6 Compact Terminals (400, 600, and 1000) Secondary Replacement Options

PanelView Plus 6 Terminals					PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Cat. No.	Panel Cutout Dimensions		Display Resolution	Adapter Plate Cat. No.	Comm.	Notes
		Height mm (in.)	Width mm (in.)			Height mm (in.)	Width mm (in.)				
400	2711PC-K4M20D8	123 (4.86)	156 (6.15)	320 x 240							
	2711PC-B4C20D8										
	2711PC-B4C20D8-LR				2711P-T4W21D8S ⁽¹⁾	92 (3.62)	117 (4.61)	480 x 272	N/A	One Ethernet Port	Low-reflective display is not available for PanelView Plus 7 Standard terminals.
600	2711PC-T6M20D8	224 (8.8)	305 (12.00)	640 x 480							
	2711PC-T6C20D8										
1000	2711PC-T10C4D8	224 (8.8)	305 (12.00)	640 x 480							

(1) This terminal does not offer a low-reflective display, but can be a replacement if a low-reflective display is not required.

Accessories

Some accessories and accessory catalog numbers are new or have changed for PanelView Plus 7 Standard and PanelView Plus 7 Performance terminals. See the accessories section in the respective user manuals that are listed in [Additional Resources on page 23](#) for a list of accessories and catalog numbers for the terminals.

Adapter Kit Conversion Table

The adapter kit provides hardware for installing a PanelView Plus 7 Performance terminal into the cutout of the existing PanelView Plus 6 terminal. See the Adapter Kit for PanelView 5500 and PanelView Plus 7 Performance Terminals, publication [VIEW-IN0002](#).

IMPORTANT These adapter kits are for PanelView Plus 7 Performance terminals.
Do not install a PanelView Plus 7 Standard terminal with these adapter kits. The bezel of the standard terminal can be damaged, which can reduce the effectiveness of the seal and damage the terminal and components that are installed in the cabinet.

Adapter Kit Cat. No.	Replace this Existing PanelView Plus 6 Terminal...	With this PanelView Plus 7 Performance Terminal
2711P-RAAT7	700 touch screen	6.5-in. touch screen
2711P-RAAK7	700 keypad, or keypad with touch screen	6.5-in. keypad with touch screen
2711P-RAAT10	1000 touch screen	10.4-in. touch screen
2711P-RAAK10	1000 keypad, or keypad with touch screen	10.4-in. keypad with touch screen
2711P-RAAT12	1250 touch screen	12.1-in. touch screen
2711P-RAAT12K	1250 keypad, or keypad with touch screen	12.1-in. touch screen
2711P-RAAT15	1500 touch screen	15-in. touch screen
2711P-RAAK15	1500 keypad, or keypad with touch screen	15-in. keypad with touch screen

Legacy Communication Support

PanelView Plus 7 terminals use only Ethernet communication. If you need support for non-Ethernet communication protocols, go to the following Encompass™ Partner websites:

- <http://www.anybus.com/products/prodindex.shtml>
- <http://www.prosoft-technology.com/Products/Gateways>

Additional Resources

These documents contain additional information concerning related products from Rockwell Automation.

Resource	Description
PanelView Plus 7 Performance Terminals User Manual, publication 2711P-UM008	Provides information on how to install, operate, configure, and troubleshoot the PanelView Plus 7 Performance terminals.
PanelView Plus 7 Performance Terminals Technical Data, publication 2711P-TD009	Provides technical specifications, environmental specifications, and certifications for the PanelView Plus 7 Performance terminals.
PanelView Plus 7 Standard Terminals User Manual, publication 2711P-UM007	Provides information on how to install, operate, configure, and troubleshoot the PanelView Plus 7 Standard terminals.
PanelView Plus 7 Standard Terminals Technical Data, publication 2711P-TD008	Provides technical specifications, environmental specifications, and certifications for the PanelView Plus 7 Standard terminals.
PanelView Plus 6 Terminals User Manual, publication 2711P-UM006	Provides information on how to install, operate, configure, and troubleshoot the PanelView Plus 6 terminals.
PanelView Plus 6 Compact Terminals User Manual, publication 2711PC-UM002	Provides information on how to install, operate, configure, and troubleshoot the PanelView Plus 6 Compact terminals.
PanelView Plus 6 Terminals Technical Data, publication 2711P-TD005	Provides technical specifications, environmental specifications, and certifications for the PanelView Plus 6 and PanelView Plus 6 Compact terminals.
Industrial Automation Wiring and Grounding Guidelines, publication 1770-4.1	Provides general guidelines for installing a Rockwell Automation industrial system.
Product Certifications website, http://www.rockwellautomation.com/global/certification/overview.page	Provides declarations of conformity, certificates, and other certification details.

You can view or download publications at <http://www.rockwellautomation.com/global/literature-library/overview.page>. To order paper copies of technical documentation, contact your local Allen-Bradley distributor or Rockwell Automation sales representative.

Important User Information

Read this document and the documents listed in the additional resources section about installation, configuration, and operation of this equipment before you install, configure, operate, or maintain this product. Users are required to familiarize themselves with installation and wiring instructions in addition to requirements of all applicable codes, laws, and standards.

Activities including installation, adjustments, putting into service, use, assembly, disassembly, and maintenance are required to be carried out by suitably trained personnel in accordance with applicable code of practice.

If this equipment is used in a manner not specified by the manufacturer, the protection provided by the equipment may be impaired.

In no event will Rockwell Automation, Inc. be responsible or liable for indirect or consequential damages resulting from the use or application of this equipment.

The examples and diagrams in this manual are included solely for illustrative purposes. Because of the many variables and requirements associated with any particular installation, Rockwell Automation, Inc. cannot assume responsibility or liability for actual use based on the examples and diagrams.

No patent liability is assumed by Rockwell Automation, Inc. with respect to use of information, circuits, equipment, or software described in this manual.

Reproduction of the contents of this manual, in whole or in part, without written permission of Rockwell Automation, Inc., is prohibited.

Documentation Feedback

Your comments will help us serve your documentation needs better. If you have any suggestions on how to improve this document, complete this form, publication [RA-DU002](#), available at <http://www.rockwellautomation.com/literature/>.

Rockwell Automation maintains current product environmental information on its website at <http://www.rockwellautomation.com/rockwellautomation/about-us/sustainability-ethics/product-environmental-compliance.page>.

Allen-Bradley, DH+, Encompass, FactoryTalk, LISTEN. THINK. SOLVE, PanelView, Rockwell Automation, and Rockwell Software are trademarks of Rockwell Automation, Inc. Trademarks not belonging to Rockwell Automation are property of their respective companies.

Rockwell Otomasyon Ticaret A.Ş., Kar Plaza İş Merkezi E Blok Kat:6 34752 İçerenköy, İstanbul, Tel: +90 (216) 5698400

www.rockwellautomation.com

Power, Control and Information Solutions Headquarters

Americas: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444
Europe/Middle East/Africa: Rockwell Automation NV, Pegasus Park, De Kleetlaan 12a, 1831 Diegem, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640
Asia Pacific: Rockwell Automation, Level 14, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846